



Technical resources

Precision air blower dryer

Model: DHG

<https://www.tencanballmills.com/en/products/sintering-series/precision-air-blower-dryer.html>

09.10.2026 / TENCAN

Precision air blower dryer

Model: DHG

Precision forced air dryer ensures uniform heating for strict temperature tests. Ideal for electronics, rubber, plastics, and materials.

Technical specifications

Temperature range	50~300°C
Power consumption	1200~5000W
Standard shelves	2 pieces

These specifications describe the series. Confirm the selected model, power supply and configuration before ordering.



The precision blast dryer is an efficient and stable hot air circulation drying equipment, which is widely used in laboratories, industrial production and scientific research fields. Its core consists of a stainless steel liner, intelligent temperature control system, forced convection fan, heating element and multiple safety protection devices. The equipment supports a temperature range usually from room temperature to 300°C (some can reach over 500°C), the temperature control accuracy can

reach $\pm 0.1^{\circ}\text{C}$, and precise adjustment is achieved through a microcomputer PID controller. Some models also have humidity control functions, which are suitable for handling materials that are sensitive to temperature and humidity.

DHG系列

产品细节

精度 $\pm 1^{\circ}\text{C}$
高度可自由调节



微电脑多编程控温仪表
具有跟踪报警功能，温控线性好

优质钢板
确保持久使用的机械精度



- **laboratory research** : Used for sample drying, glassware sterilization, material thermal stability testing, etc.
- **Industrial manufacturing**: Used in aging testing of electronic components, dehydration of chemical raw materials, drying and curing of food baking and pharmaceutical products.
- **High-tech fields**: Serving the drying process of aerospace and new energy materials (such as graphene, carbon nanotubes).

Technical parameters

model	DHG-9040J	DHG-9070J	DHG-9140J	DHG-9240J	DHG-9440J	DHG-9640J
Supply voltage	220V 50HZ				380V 50HZ	
temperature range	50~300℃					
temperature fluctuations	±1℃					
temperature uniformity	±1.5℃%					
Tracking alarm	+5℃					
Standard shelves	2 pieces					
Power consumption	1200W	1700W	2200W	2700W	4000W	5000W
Studio size (mm)	350*350*350	450*350*450	550*450*550	600*500*750	700*650*900	800*800*1000
Overall dimensions (mm)	540*500*750	640*500*850	740*600*950	790*650*1210	890*800*1360	990*950*1460

- **Heating and circulation** : The electric heating element (nickel-chromium alloy or quartz tube) generates heat, and the high-temperature-resistant fan forces the hot air to be evenly distributed to the working room to form horizontal or vertical convection.
- **Humidity control**: The evaporated moisture is discharged through air circulation. Some models feedback signals through the humidity sensor, and the control system dynamically adjusts the heating power to maintain the set humidity.
- **closed loop control**: Monitor the temperature in real time and adjust the heating power. It will automatically enter the constant temperature state after reaching the set value. Some high-end models support programmed temperature gradient control.

Contact

Changsha Tianchuang Powder Technology Co., Ltd. / Changsha, Hunan, China

Email: lichang0516@gmail.com

Phone / WhatsApp: +86 731 84027560 / WhatsApp +86 19021571516

<https://www.tencanballmills.com/en/products/sintering-series/precision-air-blower-dryer.html>

Before operation, review the selected model's instructions and the material requirements.