



Technical resources

Ultrasonic planetary ball mill

<https://www.tencanballmills.com/en/products/grinding-series/planetary-ball-mill/ultrasonic-planetary-ball-mill.html>

09.10.2026 / TENCAN

Ultrasonic planetary ball mill

Model:

Ultrasonic planetary ball mill with synergistic cavitation and acoustic flow for super-fine grinding, eliminating agglomeration in nanomaterials, new energy, and electronic ceramics.

Technical specifications

Grinding jar specification	0.5L~50L
Feed particle size	Soil ≤ 10 mm, other materials ≤ 3 mm
Output particle size	Minimum attainable 0.1 μm

These specifications describe the series. Confirm the selected model, power supply and configuration before ordering.



The ultrasonic planetary ball mill is a new generation of high-energy grinding equipment developed based on the traditional planetary ball mill and integrating an ultrasonic oscillation system. it passes **Planetary mechanical grinding and ultrasonic cavitation/acoustic flow effect** The synergistic effect simultaneously achieves ultra-fine crushing and efficient dispersion of materials, fundamentally solving the problems that are prone to occur when conventional ball mills handle micron and nanometer materials. **Sinking to the bottom, agglomeration, wall sticking, secondary agglomeration** and other process problems.

Relying on the dual energy synergy of ball mill mechanical impact + ultrasonic cavitation, acoustic flow, and high-frequency vibration, compared with ordinary ball mills, **Six outstanding advantages** :

1. Completely inhibit powder agglomeration and greatly improve the dispersion effect (the core advantage)

Ultrasonic cavitation burst generates instantaneous high temperature, high pressure, and micro jets to break the intermolecular force/electrostatic adsorption between nanoparticles and disperse them while grinding, eliminating secondary agglomeration, agglomeration, tank bottom hardening, and material sticking to the wall after fine powder grinding. ; It is especially suitable for materials that are easily agglomerated, such as lithium battery materials, rare earth powders, nano-oxides, and magnetic powders, and effectively inhibits the agglomeration of magnetic powders.

2. The grinding efficiency is increased by 30%~50%, shortening working hours, saving energy and reducing consumption.

Mechanical grinding achieves coarse crushing of particles, ultrasonic micro-tearing and refinement, double energy superposition $1+1>2$, and the grinding time is shortened by $1/3\sim 1/2$ at the same discharge fineness. ; There is no need for long-term no-load dry grinding and repeated feeding to break up agglomerations, reducing equipment energy consumption and grinding ball loss. ; The grinding speed of difficult-to-grind high-viscosity slurry and paste materials is particularly obvious.

3. The powder particle size is finer, the particle size distribution is narrow, and the product consistency is high

The limit of conventional ball milling is mostly at the micron level, and ultrasonic assistance can stably grind to the nanometer level of $50\sim 500\text{nm}$. ; Ultrasonic stirs the entire material evenly, the particles stay for even grinding time, the difference in particle size span D_{50}/D_{90} is smaller, and the powder quality is stable. It is suitable for the production of precision powders such as MLCC electronic ceramics, polishing powder, and pharmaceutical raw materials.

4. Applicable to a wider range of materials and compatible with special working conditions

Material form: dry powder, aqueous slurry, organic solvent suspension, high viscosity paste, biological wet material all-round processing ; Special process: can be used with vacuum tank and inert gas protection (nitrogen/argon) to grind easily oxidized and hydrolyzable powders ; Some models are equipped with temperature control, suitable for heat-sensitive medicine and polymer materials. ; Special materials: biological cell wall breaking, catalysts, nano zero-valent iron, phosphors and other categories that are difficult to process with traditional ball mills.

5. Reduce wear and impurity pollution

In order to break up agglomerates, traditional ball mills need to increase the filling amount of the grinding balls and increase the rotation speed, which intensifies the wear of the tank and the grinding balls and introduces metal impurities. ; Ultrasound relies on sound field dispersion, which can reduce the grinding ball ratio and rotation speed, greatly reduce powder pollution caused by media wear, and improve the yield rate of high-purity powders.

6. Easy to use and friendly operating environment

The materials in the tank continue to flow in suspension, and there is no need to stop the machine midway to open the lid, scrape the wall, or turn over the material, and the automation continuity is better. ; The models with the same specifications are compact in size and have lower operating noise than ordinary high-energy ball mills. They are suitable for small-batch research and development in laboratories and pilot mass production. They can produce multiple sets of parallel samples at a time (four tanks can be ground simultaneously). ; Ultrasound has a mild activation effect, and grinding can also assist solid phase synthesis and surface modification, realizing the integration of grinding + modification and simplifying back-end processes.





四罐研磨

可同时研磨四种不同物料，
效率高



超声波控制系统

由超声波发生器和超声波换能器组成



湿磨状态下使用

粒度研磨粒度不同，材料
各异的各类固体颗粒、悬
浮液和糊膏，研磨产品最
小粒度可至纳米级



超声波控制系统

由超声波发生器和超声波换能器组成



安全罩门

保护球磨机内部



行星机构

整体成型主盘，采用新式压杆，精致美观大方；转速稳定、效率高、研磨颗粒更细。



散热风扇孔

高速运转，有效增强机体气流流动速度，散热速度提高，保证机器有效长久的稳定运行



1、设备特点

坚实牢固，外形更加的大气



2、配置超声波设备

可实现边研磨边振动，可解决沉底、结块、粘壁、团聚的问题



3、湿磨状态下使用

粒度研磨粒度不同、材料各异的各种固体颗粒、悬浮液和糊膏，研磨产品最小粒度可至纳米级

Ultrasonic planetary ball mills are widely used in scientific research institutes, university laboratories and corporate R&D and production departments, covering many high-tech fields such as new energy, electronic ceramics, biomedicine, chemical and environmental protection.

Application areas	Typical uses
New energy materials	Ultra-fine grinding and uniform mixing of lithium battery cathode materials (lithium iron phosphate, ternary materials), silicon carbon anodes, fuel cell catalysts, etc. to improve battery energy density and consistency
Electronic ceramics and functional materials	High-precision grinding of MLCC dielectric materials, piezoelectric ceramics, magnetic materials (ferrite), rare earth polishing powder, etc., controlling the powder particle size to optimize the electrical performance of the device
Medicine and Biotechnology	Micronization of poorly soluble drugs (to improve dissolution), cell wall disruption, DNA/RNA extraction, and ultrasound assistance can reduce damage to heat-sensitive components
Chemical industry and environmental protection	Catalyst preparation and activation, nano zero-valent iron (for wastewater treatment), pigment and coating dispersion
Geology, metallurgy and others	Laboratory sample preprocessing and ultrafine crushing of brittle materials and fibrous materials such as ores, slag, glass, ceramics, etc.

This device is mainly suitable for It can handle solid particles, suspensions and paste-like materials, and has good grinding effect on brittle, fibrous and medium-low hardness materials.

Technical parameters

Transmission mode	gear transmission
working method	Two or four ball mill tanks work simultaneously
Maximum sample loading volume (material + grinding ball)	Two-thirds of the ball mill tank volume
Ball mill tank volume	Each can is 0.5L-50L, total volume is 0.2L-200L
Feed particle size	Soil material ≤10mm, other materials ≤3mm
Discharge particle size	The minimum can reach 0.1μm (different materials and grinding processes will vary)
Speed ratio (revolution:rotation)	1:2
Speed (rotation)	XQM-6Grinding tank rotation speed:0~670rpm For more details, see the main parameters of planetary ball mill
Speed regulation method	Brand inverter stepless speed regulation

Ultrasonic planetary ball mill adopts“ **Planetary mechanical grinding + ultrasonic assisted dispersion** ”Dual crushing mechanism, the two energies are superimposed simultaneously in time and space to achieve efficient collaboration.

1. Planetary mechanical grinding (macro crushing)

The main disk of the equipment revolves around the central spindle, and the ball mill tank installed on the main disk rotates around its own axis at high speed at the same time. The speed ratio

between revolution and rotation is usually 1:2. This composite motion causes the grinding balls and materials in the tank to be subjected to multi-directional and high-frequency vibrations. **Impact, Shear and Friction** effect:

- The grinding ball hits the material at extremely high speed in a high centrifugal force field to break large particles.;
- The sliding friction and shearing between the grinding balls and between the grinding balls and the tank wall further refine the particles.;
- The three-dimensional movement generated in the tank ensures that the material contacts the grinding media without any dead ends.

This process can quickly crush materials from millimeter level to micron or even sub-micron level.

2. Ultrasonic assisted dispersion (microscopic depolymerization)

The ultrasonic system consists of a generator, a transducer and a conductive slip ring. The generator converts power frequency electricity into high-frequency electrical oscillation (common frequency 20kHz ~ 40kHz), and the transducer converts it into mechanical vibration, which is transmitted to the inner wall of the rotating grinding tank through the conductive slip ring, causing the liquid medium to generate high-frequency mechanical waves. There are two main effects:

- **cavitation effect** : Ultrasonic waves alternately produce tension and compression in the liquid. A large number of tiny bubbles are formed during stretching, and the bubbles instantly collapse during compression, generating local shock waves with high temperatures of thousands of degrees Celsius and hundreds of atmospheric pressures, breaking up the refined particle agglomeration structure and preventing secondary agglomeration.
- **Acoustic flow effect** : Ultrasonic waves cause the macroscopic circulation flow of the liquid, keeping the materials in the tank in a state of motion, effectively preventing dense particles from sinking to the bottom or adhering to the tank wall, and ensuring grinding uniformity.

3. Synergy mechanism


Planetary motion provides continuous mechanical impact from the outside to continuously crush the particles; Ultrasonic waves continuously exert "anti-agglomeration force" from the inside, disintegrating each agglomerate before it is stable. The synchronized effect of the two greatly shortens the grinding time required to reach the target particle size, significantly improves the uniformity of the discharged particle size distribution, and enables the minimum discharged particle size to reach the nanometer level. This mechanism cannot be realized by traditional ball mills, and it is also the core technology that distinguishes ultrasonic planetary ball mills from ordinary planetary ball mills.

研磨系列

行星球磨机/配件介绍




不锈钢球



氧化铝球



氧化锆球



玛瑙球



聚氨酯球



硬质合金球

我们还可以提供各种磨球:不锈钢球、氧化锆球、氧化铝球、PU球、钢碳球、钨球、玛瑙球、硬质合金球、氮化硅球、高耐磨钢球, 锰钢球、尼龙球、硬质合金、玻璃和其他特种金属材料。



不锈钢研磨球



刚玉研磨球



聚氨酯研磨球



聚四氟研磨罐



玛瑙研磨球



尼龙研磨球



氧化锆研磨球



硬质合金研磨球

我们还可以提供各种材质球磨罐: 玛瑙、氧化铝刚玉陶瓷、氧化锆陶瓷、氮化硅陶瓷、碳化硅陶瓷、不锈钢、耐磨钢、锰钢、尼龙、聚氨酯、硬质合金、水晶玻璃等。

Contact

Changsha Tianchuang Powder Technology Co., Ltd. / Changsha, Hunan, China

Email: lichang0516@gmail.com

Phone / WhatsApp: +86 731 84027560 / WhatsApp +86 19021571516

<https://www.tencanballmills.com/en/products/grinding-series/planetary-ball-mill/ultrasonic-planetary-ball-mill.html>

Before operation, review the selected model's instructions and the material requirements.